

OPERATION & MAINTENANCE

Push self-closing disposal door to deposit waste material. Seat covers are self-feeding until supply is depleted. Toilet paper rolls feed freely until depleted and level of supply is constantly visible for low-level warning. Waste receptacle is emptied manually on cycle determined by maintenance needs. Toilet paper rolls, paper seat covers and waste receptacle are serviced by unlocking and opening door. Locked door prevents inadvertent dumping and unauthorized removal. Waste container safetyedged finger hole provides convenient grip for service. Toilet paper spindles are carried in vandal resistant sub-frame accessible when door is opened.

TECHNICAL INFORMATION / PRODUCT PROPERTIES

Property	Value
Dimensions	17-3/8" x 30-5/8" x 4-1/4" [441 x 508 x 108]
Construction	Type 304 Stainless Steel - Satin Finish 18 gauge Door with Multi-staked piano hinge
Mounting	Recessed
Capacity	1,000 seat covers / 2 Tissue Rolls / 1.3 gal (4.9 L) Waste Capacity

INSTALLATION

Mount unit in wall recess using four (4) #10 self-threading screws (by others) through concealed mounting holes provided. Note that top of Rough Wall Opening (RWO) is 13/16" [21] below top of unit. For ADAAG compliance the centerline of the TP Dispenser should be located within 7" [178] to 9" [227] of the front of the toilet and the TP Dispenser opening bottom should be above 15" [381] minimum Above Finished Floor (AFF) while the Seat Cover Dispenser opening centerline should be no higher than 48" [1219] maximum AFF. An optional GB (not provided) at 33" to 36" [838 to 914] AFF to the top of the bar should allow the service door top to clear the bottom of the bar when opening the door. Rough Wall Opening (RWO) required is 15-3/4" W x 29" H x 4" D minimum [400 x 737 x 102]

ADDITIONAL INFORMATION

WARRANTY

One (1) Year from date of Invoice