



OR2200LCDRTL2U SMART APP LCD UPS



Cost-effective feature-rich power protection for networking, servers and telecommunications equipment.

A rack/tower convertible UPS with line interactive topology, the CyberPower Smart App LCD OR2200LCDRTL2U provides battery backup (using simulated sine wave output) and surge protection for department servers, workgroup servers, workstations, network devices, and telecom installations without active PFC power supplies.

The OR2200LCDRTL2U uses Automatic Voltage Regulation (AVR) to correct minor power fluctuations without switching to battery power, which extends battery life. AVR is essential in areas where power fluctuations occur frequently. This model accepts the RMCARD205 network management card for remote management and control via a standard web browser or network management system.

The OR2200LCDRTL2U comes with a three-year warranty and a \$300,000 Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Servers
- Workstations
- Network Devices
- Telecom Equipment

FEATURES

- 2100VA / 1650W
- Line Interactive Topology
- Automatic Voltage Regulation (AVR)
- GreenPower UPS™
- 2U Rack Mount/Tower Convertible
- Multifunction Rotatable LCD
- SNMP/HTTP Remote Management
- 8 Outlets / USB, Serial, and EPO Ports
- EMI/RFI Filters
- PowerPanel® Business Software
- 3-Year Warranty

SPECIFICATIONS

GENERAL

UPS Topology	Line Interactive
Energy Saving	GreenPower UPS™ Bypass Technology

INPUT

Voltage	90 - 140 VAC
Frequency Range	47 - 63 Hz
Plug Type	NEMA 5-20P
Plug Style	Straight
Cord Length	10 ft

OUTPUT

VA	2,100 VA
Watts	1,650 W
Automatic Voltage Regulation	Yes
On Battery Voltage	120 VAC ± 5%
On Battery Frequency	60 Hz ± 1%
On Battery Waveform	Simulated Sine Wave
Outlet Type	NEMA 5-20R
Outlets - Battery & Surge Protected	8

OR2200LCDRTL2U SMART APP LCD UPS



SPECIFICATIONS CONT.

OUTPUT CONT.

Overload Protection Internal circuitry limiting / circuit breaker

Transfer Time 4 ms

BATTERY

Runtime at Half Load (min) 15

Runtime at Full Load (min) 6

Battery Type Sealed Lead-Acid

Battery Size 12V/9Ah

Battery Quantity 4

Hot-Swappable Yes

User Replaceable Yes

Replacement Battery Cartridge RB1290X4B

Replacement Battery Cartridge Quantity 1

Typical Recharge Time 8 hours

Extended Battery Option BP48VP2U02

SURGE PROTECTION & FILTERING

Surge Suppression 2,060 J

Network Protection RJ45 1-in / 1-out (10/100/1000)

Coax Protection RG6 1-In, 1-Out

EMI/RFI Filtration Yes

MANAGEMENT & COMMUNICATIONS

Multifunction LCD Yes

HID Compliant USB Port Yes

Serial Port Yes

Management Cable USB Cable

LED Indicators Power On, Wiring Fault

Audible Alarms Battery Mode, Low Battery, Overload, Fault

Software (Free Download) PowerPanel® Business

SNMP / HTTP Remote Monitoring Yes, with optional RMCARD205

PHYSICAL

Rack Size 2U

Form Factor Mini-Tower

Dimensions (WxHxD) (in.) 3.9 x 9.7 x 10.2

Weight (lbs.) 15.0

ENVIRONMENTAL

Operating Temperature 32 °F to 104 °F / 0 °C to 40 °C

Operating Humidity 0% - 90% non-condensing

CERTIFICATIONS

Safety UL1778, cUL 107.3, FCC DOC Class B

Environmental RoHS Compliant

WARRANTY

CEG Amount \$300,000

Product Warranty 3 Years Limited

Connected Equipment Guarantee Lifetime