

PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

2510 LEVER - PASSAGE - F75

2510



SPECIFICATIONS

Applications

Backsets

Certifications

Door Thickness

Exposed Trim

Features

Finishes

Functions

Latchbolt Type

Lever Options

Lock Chassis

Options

Strikes

Rose Diameter Standard Door Prep 3-11/32" (85mm)

• Standard door prep - 2-1/8" (54 mm) diameter (cross bore)

• 1-1/8" x 2-1/4" (29 mm x 57 mm) faceplate for 2-3/4" (70 mm) backset • 1" x 2–1/4" (25 mm x 57 mm) faceplate for 2–3/8" (60mm) backset

• Heavy gauge steel, zinc dichromated for corrosion resistance.

• Failure to install thru-posts and screws voids BHMA certification, UL rating, and

• Latch hole - 1" (25 mm) diameter (edge bore)

1-1/4" x 4-7/8" (32 mm x 124 mm) ASA strike

Additional latchbolts and strikes available.

Standard Duty Commercial

• 2-3/4" (70 mm) standard • 2-3/8" (60 mm) optional

• UL10C Positive Pressure Rated

• No exposed mounting screws

• 1/2" (13 mm) throw, stainless steel

• Thru-posts are removable.

1-3/8" - 2" (35mm - 51mm)

• Non-handed

Passage (F75)

Archer and Withnell

warranty.

US3, US10B, US26D and BLK

• ADA Compliant ANSI A117.1 Accessibility Code

Meets BHMA A156.2 Grade 2 test standards

• Wrought brass, bronze, and stainless steel

• Lever is zinc based, plated to match BHMA symbols

• UL/cUL Listed for all functions up to 3 hours "A" label single doors



2510 LEVER - PASSAGE - F75

Warranty

5-year