



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

2525 LEVER - EXIT - F111

2525



SPECIFICATIONS

Applications	<ul style="list-style-type: none">• Standard Duty Commercial•
Backsets	<ul style="list-style-type: none">• 2-3/4" (70 mm) standard• 2-3/8" (60 mm) optional
Certifications	<ul style="list-style-type: none">• ADA Compliant ANSI A117.1 Accessibility Code• UL/cUL Listed for all functions up to 3 hours "A" label single doors• UL10C Positive Pressure Rated• Meets BHMA A156.2 Grade 2 test standards
Door Thickness	1-3/8" - 2" (35 mm - 51 mm)
Exposed Trim	<ul style="list-style-type: none">• Wrought brass, bronze, and stainless steel• Lever is zinc based, plated to match BHMA symbols
Features	<ul style="list-style-type: none">• No exposed mounting screws• Non-handed
Finishes	US3, US10B, US26D and BLK
Functions	Exit (F111)
Latchbolt Type	<ul style="list-style-type: none">• 1/2" (13 mm) throw, stainless steel• 1-1/8" x 2-1/4" (29 mm x 57 mm) faceplate for 2-3/4" (70 mm) backset• 1" x 2-1/4" (25 mm x 57 mm) faceplate for 2-3/8" (60mm) backset• Deadlocking latchbolt prevents manipulation when door is closed
Lever Options	Archer and Withnell
Lock Chassis	Heavy gauge steel, zinc dichromated for corrosion resistance. Thru-posts are removable. Failure to install thru-posts and screws voids BHMA certification, UL rating, and warranty
Notes	Blank plate projection is 13/16" (21 mm) for function 25
Options	Additional latchbolts and strikes available.
Rose Diameter	3-11/32" (85 mm)
Standard Door Prep	<ul style="list-style-type: none">• Standard door prep - 2-1/8" (54 mm) diameter (cross bore)• Latch hole - 1" (25 mm) diameter (edge bore)

Strikes	1-1/4" x 4-7/8" (32 mm x 124 mm) ASA strike
Warranty	5-year