



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

282D

282D

Must be ordered in increments of two.



SPECIFICATIONS

Bolt	Backset: 3/4" (19 mm)
Bolt Throw	3/4" (19 mm)
Certifications	Three-hour fire rating for metal doors up to 4' wide by 10' tall Meets ANSI 156.16 for LO4251
Faceplate	1" x 6-3/4" (25 mm x 171 mm)
Fasteners	Eight #8 x 3/4" combo screws, Eight #8 x 1-1/2" combo screws
Finishes	US3, US4, US5, US9, US10, US10B, US15, US15A, US19, US26, US26D
Guide Plate Height	2" (51 mm)
Guide Plate Width	1" (25 mm)
Material	Brass faceplate with steel components
Mortise Strike Length	2-1/4" (24 mm x 57 mm)
Mortise Strike Width	15/16" (24 mm)
Notes	<ul style="list-style-type: none">• Priced as each and sold in increments of two• 282S strike plate bag and 282P bolt head available• For use on hollow metal/fire rated doors• Non-handed• Bolt heads are adjustable• Bolt head, if required, may be ordered as part 282P
Optional Features	Rod Length: 18" (457 mm), 24" (610 mm), 30" (762 mm)- Specify 282R
Product Description	Manual Flush Bolt for Metal Doors
Rod Length	12" (305 mm) from center of face to corner of door