



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

311H

311H



SPECIFICATIONS

Bolt Diameter	3/4" (19 mm)
Bolt Throw	1/2" (13 mm)
Box Quantity	1
Case Quantity	10
Certifications	ANSI A156.2 closest equivalent (bored latch- series 4000- grade 2)
Door Thickness	1-3/4" (45 mm)
Escutcheons	3-1/16" x 5" (78 mm x 127 mm)
Finishes	US26, US26D, US32, US32D
Material	Zinc, Stainless Steel
Notes	<ul style="list-style-type: none"> • 2-3/4" (70 mm) backset standard, 5" (127 mm) backset optional • Non-handed
Optional Features	Engraving Handed: A (standard) - "PUSH" down; "PULL" down. B - "PUSH" up; "PULL" down. C - "PUSH" up, "PULL" up. D - "PUSH" down, "PULL" up.
Product Description	Push/Pull Hospital Latch
Projection	2-5/8"
Push & Pull Levers	1-15/16" x 4-1/2" (49 mm x 114 mm)
Strike Size	1-1/8" x 2-3/4" (57 mm x 29 mm) T-strike and 1-1/4" x 4-7/8" (124 mm x 32 mm) ASA strike are both included