



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

3216 - THUMBTURN X OCCUPANCY INDICATOR

3216



SPECIFICATIONS

Applications	Standard Duty Commercial
Backsets	Adjustable 2-3/8" - 2-3/4" (60mm - 70 mm)
Certifications	<ul style="list-style-type: none"> • ADA Compliant ANSI A117.1 Accessibility Code • BHMA Certified ANSI A156.36, Grade 2
Deadbolt	<ul style="list-style-type: none"> • 1" (25 mm) Throw - Brass with concealed hardened steel roller to prevent sawing or cutting • 1-1/8" x 2-1/4" (29 mm x 57 mm) square corner faceplate
Door Thickness	1-3/4" (45 mm)
Exposed Trim	Wrought Brass, Bronze or Stainless Steel
Finishes	US3, US4, US10B, US26D and US32D
Functions	Thumbturn x Occupancy Indicator
Notes	Non-handed
Options	<ul style="list-style-type: none"> • Split Finish • Additional Deadbolts and strikes available
Strikes	<ul style="list-style-type: none"> • 3930 - 1-1/8" x 2-3/4" (29 mm x 70 mm) no-lip strike - standard • 3929 - 1-1/4" x 4-7/8" (32 mm x 124 mm) ASA deadbolt strike - optional
Warranty	Lifetime