



## PRODUCT SPECIFICATIONS

For more information visit [www.hagerco.com](http://www.hagerco.com)

### 3450 - OFFICE - F82A

3450



## SPECIFICATIONS

### Applications

- Extra Heavy Duty Commercial
- Industrial
- Institution

### Backsets

- 2-3/4" (70mm) - Standard
- 2-3/8" (60mm) - Optional
- 3-3/4" (94mm) - Optional
- 5" (128mm) - Optional

### Certifications

- ADA Compliant ANSI A117.1 Accessibility Code
- UL/cUL Listed for all functions up to 3 hours "A" label single doors
- UL10C Positive Pressure Rated
- BHMA Certified ANSI A156.2, Series 4000, Grade 1
- ANSI A250.13 Severe Windstorm Compliant
- Miami Dade County, FL NOA #22-0816.08

### Cylinders/Cores

- Keyed Different - standard
- Cylinder drilled 6 pin, Keyed 5 pin - standard
- Other Keying options, including 6 pin keyed, available from factory
- Zero bit cylinders will be 6 pin keyed
- SFIC uncombined or combined, brass 6 pin or 7 pin cores sold separately
- LFIC Zero-Bit or combined, brass 6 pin cores sold separately

### Door Thickness

1-3/8" - 2" (35 mm - 51 mm)

### Exposed Trim

- Wrought brass, bronze, and stainless steel
- Lever is zinc based, plated to match BHMA symbols

### Features

- No exposed mounting screws
- Non-handed

### Finishes

- US3, US4, US10B, US26, US26D and BLK
- Anti-Microbial Coating (US26D finish only)

### Functions

Office (F82A)

### Keyway

Schlage C - Standard, Other keyways optional

### Latchbolt Type

- 1/2" (13 mm) throw, stainless steel
- 1-1/8" x 2-1/4" (29 mm x 57 mm) faceplate
- Deadlocking latchbolt prevents manipulation when door is closed
- 3/4" (19 mm) throw latchbolt available

**Lever Options**

Archer, August and Withnell

**Lock Chassis**

- Heavy gauge steel, zinc dichromated for corrosion resistance.
- Thru-post mounted.

**Notes**

- SFIC option available (Cores are sold separately - standard)
- LFIC option available (Cores sold separately - standard)

**Options**

- Lead Lining
- Tactile Warning
- Split Finish

**Rose Diameter**

3-17/32" (90 mm)

**Standard Door Prep**

- 2-1/8" (54 mm) diameter with thru-bolt holes (cross bore)
- Latch hole - 1" (25 mm) diameter (edge bore)

**Strikes**

- 1-1/4" x 4-7/8" (32 mm x 124 mm) ASA strike
- Optional strikes available

**Warranty**

Lifetime