



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

3550 - OFFICE - F82A

3550 LEVER



BHMA



cUL US LISTED



SPECIFICATIONS

Applications

Standard Duty Commercial

Backsets

- 2-3/4" (70mm)
- 2-3/8" (60mm)
- 3-3/4" (94mm)
- 5" (128mm)

Certifications

- ADA Compliant ANSI A117.1 Accessibility Code
- UL/cUL Listed for all functions up to 3 hours "A" label single doors
- UL10C Positive Pressure Rated
- BHMA Certified ANSI A156.2, Series 4000, Grade 2
- ANSI A250.13 Severe Windstorm Compliant (Levers)

Cylinders/Cores

- Keyed Different - standard
- Cylinder drilled 6 pin, Keyed 5 pin - standard
- Other Keying options, including 6 pin keyed, available from factory
- Zero bit cylinders will be 6 pin keyed
- SFIC uncombined or combined, brass 6 pin or 7 pin cores sold separately

Door Thickness

1-3/8" - 2" (35 mm - 51 mm)

Exposed Trim

Wrought brass, Bronze, and Stainless steel

Finishes

- US3, US4, US10B, US26, US26D and BLK
- Anti-Microbial coating (US26D finish only)

Functions

Office (F82A)

Keyway

Schlage C - Standard, other keyways optional

Latchbolt Type

- 1/2" (13 mm) throw, stainless steel
- 1-1/8" x 2-1/4" (29 mm x 57 mm) faceplate for 2-3/4" (70 mm) backset
- 1" x 2-1/4" (25 mm x 57 mm) faceplate for 2-3/8" (60 mm) backset
- Deadlocking latchbolt prevents manipulation when door is closed

Lever Options

Archer, August and Withnell

Lock Chassis

Heavy gauge steel, zinc dichromated for corrosion resistance. Thru-posts are removable. Failure to install thru-posts and screws voids BHMA certification, UL rating, and warranty

Notes

- No exposed mounting screws

- Non-handed

Options

- Lead Lining
- Tactile Warning
- Split Finish

Rose Diameter

3-11/32" (85 mm)

Strikes

- 1-1/4" x 4-7/8" (32 mm x 124 mm) ASA strike
- Optional strikes available

Warranty

Lifetime