



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

4600 SERIES RIM

4600 RIM



BHMA
A118.1



UL
LISTED



SPECIFICATIONS

Applications	Heavy Duty Commercial
Certifications	<ul style="list-style-type: none"> • ANSI/BHMA A156.3–2014 Grade 1 • UL305 Listed for Panic Hardware • UL/cUL Listed for up to 3 hours for "A" labeled doors • UL10C Positive Pressure Rated • UL10B Neutral Pressure Rated • Warnock Hersey listed for up to 3 hours with fire rated removable mullion • Complies with ANSI 117.1 for accessible buildings and facilities
Cover	Stainless steel, zinc
Cover Tube	Aluminum
Dogging	<ul style="list-style-type: none"> • Hex dogging feature standard on panic-rated labeled doors • Cylinder dogging available on panic rated devices - specify "CD". 3902 Mortise cylinder with standard cam sold separately. Cylinder Length of 1–1/8" (29mm) – 1–3/8" (35mm) is required.
Door Thickness	1–3/4" (44 mm) – Standard
Door Width	<ul style="list-style-type: none"> • 36" (914mm) field sizeable to 30" (762mm) panic-rated door and 28" (711mm) fire-rated door • 48" (1219mm) field sizeable to 36" (914mm) panic- or fire-rated door
End Caps	Zinc (Flush end cap standard)
Fasteners	<ul style="list-style-type: none"> • Wood and machine screws • Thru-bolts
Finishes	<ul style="list-style-type: none"> • US3, US4, US10B, US26, US26D, US32D, BLK • Trim not available in US32D
Functions	<ul style="list-style-type: none"> • 01 – Exit Only (device) • 02 – Dummy, pull when device is dogged down (46DT) • 03 – Night Latch, key retracts latch bolt (46NL) • 08 – Cylindrical Escutcheon, key locks or unlocks lever (46CE) • 14 – Blank Escutcheon, always operable (passage) (46BE)
Latchbolt Type	<ul style="list-style-type: none"> • Top – 1/2" (13mm) throw, stainless steel • Bottom – 1/2" (13mm) throw, held retracted during door swing, stainless steel
Notes	Recommended to be used on appropriately reinforced doors
Product Description	4600 Series Grade 1 Narrow Stile Exit Device
Projection	<ul style="list-style-type: none"> • 3" (76mm) in undogged position • 2–5/8" (67mm) in dogged position
Push Bar	OPTIONAL: Photoluminescent push bar cover available
Stile Width	<ul style="list-style-type: none"> • 2–1/8" (54mm) - Minimum stile width required for 1/2" (13mm) blade stop frame and 4950 blade stop strike • 3–1/4" (83mm) - Minimum stile width required for single door, 5/8" (16mm) stop and 4920 standard strike • 3–3/4" (95 mm) - Minimum stile width required for double door x mullion x 4920 strike • 2–3/4" (70 mm) - Minimum stile width required for double doors with 2" (51mm) mullion and 4952 semi-flush mount strike • All stile widths are measured from door edge

Strikes

- Blade stop (4950) - Standard with panic device
- Fire-rated strike (4920F) - Standard with fire-rated device
- Standard strike (4920) - Optional
- Single rabbit strike (4951) - Optional
- Semi-flush mount strike (4952) - Optional

Trim

Archer, August, William or Withnell lever with escutcheon trim

Warranty

Lifetime