



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

5100 CLOSER X TRI-PACK ARM -
STANDARD

5100 TriPack



SPECIFICATIONS

Accessories	<ul style="list-style-type: none">• Grade 1 heavy duty surface door closer adjustable sizes 1–6• Ideal for schools, hospitals, and other high-use environments
Box Quantity	1
Case Quantity	4
Certifications	<ul style="list-style-type: none">• BHMA Certified ANSI A156.4, adjustable sizes 1–6• ADA compliant ANSI A117.1 Accessibility Code• UL/cUL Listed for up to 3 hours• UL10C Positive Pressure Rated• UL10B Neutral Pressure Rated• 5100 Door Closer EPD
Door Thickness	<ul style="list-style-type: none">• 1–3/4" (44 mm) - standard• 1–3/8" - 2–1/4" (36 mm - 57 mm) thick door - optional
Fasteners	<ul style="list-style-type: none">• Self-reaming, self-tapping wood and machine screws• Sex nuts and bolts
Finishes	<ul style="list-style-type: none">• ALM, BLK, BRZ, DBZ, GOL• Rust inhibiting primer - Standard
Handing	Non-handed
Material	Cast iron, treated with rust inhibiting primer - standard
Maximum Door Weight	330 lbs.
Notes	<ul style="list-style-type: none">• To maximize hinge life and assist in achieving ADA compliance, Hager recommends the use of anti-friction or ball bearing hinges with our door closer products• The recommended temperatures for prolonged closer use is between -40° F (-42° C) and 150° F (66° C)• Any certified BHMA/ANSI A156.4 door closer, regardless of manufacturer, that is installed and adjusted based on ADA or other reduced opening force requirements may not provide sufficient power to reliably close and latch a door• If arms are ordered separately, there will be a significant difference in price than if purchased with a closer as a complete assembly. See adders for more information (add the list price of the option to the list price of the closer and take standard discounts)• Accessories may not be available in all finishes. Please contact Hager for availability and lead time

Product Description

Grade 1 Heavy Duty Surface Door Closer

Springs

- One piece seamless steel spring tube
- Double heat-treated, steel-tempered springs
- Precision-machined, heat-treated steel piston

Valves

- Adjustable backcheck, sweep, and latching valves- standard
- All valves are staked

Warranty

Lifetime warranty