



## PRODUCT SPECIFICATIONS

For more information visit [www.hagerco.com](http://www.hagerco.com)

# 6000 SERIES MEDIUM DUTY SURFACE MOUNT

6000 MDSM



## SPECIFICATIONS

<b>Applications</b>	<ul style="list-style-type: none"> <li>• 6015S- Surface friction</li> <li>• 6016S- Surface stop only</li> <li>• 6017S- Surface hold open</li> </ul>
<b>Box Quantity</b>	1
<b>Case Quantity</b>	6
<b>Certifications</b>	<ul style="list-style-type: none"> <li>• BHMA &amp; ANSI 156.8 Compliant</li> <li>• UL/cUL Listed for up to 3 hours (stop only)</li> <li>• UL10C Positive Pressure Rated (stop only)</li> <li>• UL10B Neutral Pressure Rated (stop only)</li> </ul>
<b>Door Thickness</b>	<ul style="list-style-type: none"> <li>• 1-3/4" (44 mm) thick door - standard</li> <li>• 1-3/8" - 2-1/4" (36 mm - 57 mm) thick door - optional</li> </ul>
<b>Fasteners</b>	Standard screw packet included for wood or metal door and frame applications
<b>Finishes</b>	<ul style="list-style-type: none"> <li>• US10B, US32D (for stainless steel), ALM</li> </ul>
<b>Material</b>	Steel, stainless steel
<b>Mounting Style</b>	Surface
<b>Notes</b>	<ul style="list-style-type: none"> <li>• Adjustable arms provide easy installation</li> <li>• Slide track design</li> <li>• Adjustable in the field</li> <li>• Heavy shock absorber spring provides 5° to 7° compression before dead stop</li> <li>• Special templating upon request</li> <li>• Single acting doors only</li> <li>• Degree of opening is fully adjustable and can be adapted to changing needs between 85° to 110°</li> </ul>
<b>Product Description</b>	Grade 2 Medium Duty Overhead Door Holder and Stop
<b>Size</b>	<ul style="list-style-type: none"> <li>• Size 1 (SZ1) = 20" -33" door</li> <li>• Size 2 (SZ2) = 33" -51" door</li> </ul>
<b>Warranty</b>	Five years