



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

9850HD

9850HD



SPECIFICATIONS

Available Sizes	9850HD-96" 9850HD-102"
Case Quantity	1
Certifications	<ul style="list-style-type: none">Meets performance requirements of ANSI/BHMA 156.14 (Grade 1) for sliding doors by exceeding 100,000 cycles in operation.Type: D02311-250ADA Compliant
Door Specifications	Up to 4'0" (1219 mm) wide and 8'0" (2438 mm) high
Door Thickness	For doors 1-3/8" - 1-3/4" (35 mm - 44 mm) thick
Installation	<ul style="list-style-type: none">For Bi-Parting Doors use Hager Double Pocket Door Kit 9639 (sold separately)Joins 2 pocket door frames to make one large doorway. Rough opening width changes to 4 times one door width
Maximum Door Weight	250 lbs. (113 kg)
Notes	Compares to: Stanley PDF250, Lawrence PF619
Options	<ul style="list-style-type: none">Soft Close mechanism (1-269-8651) is available, sold separately.See Related Files for additional information.Available in 102" (2591 mm) at an extended lead time. Please contact Hager customer service for additional details.
Product Description	For 4'0" wide x 8'0" high doors, up to 250 lbs. (113 kg) per door.
Size	See size option chart under Related Files
Specifications	<ul style="list-style-type: none">Heavy-Duty, V-groove, jump-proof aluminum trackPre-assembled header assembly goes up quicklyEasy door installation and removal for painting and repair3 pair of wood split studs with wood inserts - size 3/4" (19 mm) x 1-5/8" (26 mm) length relative to heightSteel encased for rigidity and to prevent fastener penetration into the pocketTrack header unit attaches to rough framing at both endsSplit studs can be nailed or screwed to track header