



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

BB1279

BB1279



SPECIFICATIONS

Additional Options	Example of Link to Another product
Applications	For use on medium weight doors or doors requiring medium frequency service
Box Quantity	3
Case Quantity	24
Certifications	ANSI A8112
Electric Modifications	EMN (Electric Monitor Only), ETW (Electric Through-Wire Only), ETM (Electric Through-Wire with Monitoring), Quick Connect
Features	Two ball bearings. Non-rising removable pin with button tip and plug.
Finishes	<ul style="list-style-type: none">L1, LS, H2H, USP, US3, US4, US10, US10A, US10B, US15, US26, US26DAdditional finishes may be available, please contact Hager for availability and lead time.
Fire Rating	Complies with NFPA80 requirements for use on fire rated door assemblies
Gauge	See Sizing Chart Options
Height	See Sizing Chart Options
Knuckles	5
Material	Steel with Steel Pin
Notes	Available with reversible hole pattern.
Options	<ul style="list-style-type: none">3-1/2" x 3-1/2" (89 mm x 89 mm) available with reversible hole patternNRP (Non-removable pin)Stamped with UL logo when ordered for exportHospital tip
Width	See Sizing Chart Options