

130NSS, 122NSS Stainless Steel Neoprene Perimeter Seal

PRODUCT CUT SHEET

Material

Stainless Steel Type 304

Synthetic EPDM Rubber in Polypropylene Thermoplastic Matrix Closed Cell Advanced Elastomeric Foam Color is Black

- Very Good Abrasion Resistance, Tensile Strength and Memory
- Flame-Resistant
- Moisture-Resistant
- > Temperature Range -81°F to 275°F
- Sood Resistance to Ozone, Sunlight and Aging
- BHMA Certified to ANSI/BHMA A156.22 Performance Tests for Heat and Cold
- ♦ #6 x ¾" Stainless Steel SMS Furnished
- Screw Holes Slotted for Adjustment

Finishes

Brushed #4 Finish (US32D, 630)

122NSSMicrocellular EPDM130NSSMicrocellular EPDM



NATIONAL GUARD PRODUCTS, INC.


MEMPHIS

4985 East Raines Road Memphis, TN 38118 **CARSON CITY** 3689 Arrowhead Drive Carson City, NV 89706

Fax: (800) 255-7874 Email: info@ngp.com

Quotes: quotes@ngp.com Orders: orders@ngp.com

PROJECT:	
SUBMITTED BY:	
DATE:	
NOTES:	



NGP-GKT-130NSS-PCS-1223-A

