




139SP

Solid Metal
Astragal



*See ngp.com for
All Applicable
Certifications for
this Product.*



POSITIVE PRESSURE
TESTED GASKETING
MATERIALS FOR
FIRE DOORS FOR
APPLICATION TO
HOLLOW-METAL-
TYPE FIRE DOORS
RATED UP TO 3
HOURS AND WOOD-
TYPE FIRE DOORS
RATED UP TO
1½ HOURS.
CATEGORY J

S

M

A

F

ngp.com

1-800-NGP-RUSH

FAX:

(800) 255-7874

QUOTES:

quotes@ngp.com



INSTALLATION INSTRUCTIONS



139SP

1. Cut astragal to fit.
2. Position on door face with astragal overlapping gap and other door a minimum of $\frac{3}{4}$ " (required by U.L. on fire-rated doors).
3. Mark screw holes.
4. Drill pilot holes for screws using a $\frac{11}{64}$ " drill bit.
5. Install with #12x1 $\frac{1}{4}$ " SMS.
6. Adjust position so astragal does not impede proper closing and latching of door.

ngp.com

1-800-NGP-RUSH

FAX: (800) 255-7874

QUOTES: quotes@ngp.com

MEMPHIS

4985 East Raines Road

Memphis, TN 38118

CARSON CITY

3689 Arrowhead Drive

Carson City, NV 89706