

## 160S, 152S, 156S, 162S Silicone Dense Bulb Seal

## PRODUCT CUT SHEET

ľ	Ла	te	ria	1

Aluminum Alloy 6063, T5 Temper Synthetic Rubber Polymer: Siloxane Dense Silicone is Black

- Excellent Flexibility and Memory
- Flame-Resistant
- Moisture-Resistant
- Temperature Range -100°F to 500°F, Remains Flexible at Extreme Temperatures
- Excellent Resistance to Ozone, UV and Aging
- Recommended for Areas Using FM200 or Halon Fire Suppression Systems
- BHMA Certified to ANSI/BHMA A156.22 Performance Tests for Heat, Cold, Air Infiltration and Smoke Infiltration
- #6 x ¾" Stainless Steel SMS Furnished
- Screw Holes Slotted for Adjustment

## Options

FATT - Fast Attach Tape



## NATIONAL GUARD PRODUCTS, INC.

MEMPHIS

4985 East Raines Road Memphis, TN 38118 **CARSON CITY** 3689 Arrowhead Drive Carson City, NV 89706

Fax: (800) 255-7874

Quotes: quotes@ngp.com Orders: orders@ngp.com


PRUJECT:	
FIIUJLUI.	

SUBMITTED BY:

DATE:

NOTES:

PRODUCT#	FINISH
152S	Mill Al
152SA	Anodized Al
152SDKB	Dark Bronze
156S	Mill Al
156SDKB	Dark Bronze
160S	Mill Al
160SA	Anodized Al
160SDKB	Dark Bronze
162S	Mill Al
162SA	Anodized Al
162SDKB	Dark Bronze



NGP-GKT-160S-PCS-1123-A

