



# NGP

# 426E

Aluminum  
Saddle Threshold  
 $\frac{1}{2}$ " x 6"



- ▶ Aluminum Alloy 6063, T5 Temper
- ▶ 6" Wide x  $\frac{1}{2}$ " Tall
- ▶ Fluted Top
- ▶ Typical Wall Thickness: .109"
- ▶ Weight: .90 Lbs./Ft.
- ▶ #10 x  $1\frac{1}{2}$ " FH Zinc Plated Wood Screws Included



**BHMA**  
CERTIFIED



POSITIVE PRESSURE TESTED GASKETING MATERIALS FOR FIRE DOORS. FOR APPLICATION TO HOLLOW-METAL-TYPE FIRE DOORS, RATED UP TO 3 HOURS AND WOOD-TYPE FIRE DOORS, RATED UP TO  $1\frac{1}{2}$  HOURS. CATEGORY J

**ngp.com**  
**1-800-NGP-RUSH**

FAX: (800) 255-7874  
QUOTES: [quotes@ngp.com](mailto:quotes@ngp.com)

10.23

# THRESHOLD

---

# INSTALLATION INSTRUCTIONS

---

1. Cut threshold to size required.
2. Notch around door frame if desired.
3. Attach to floor surface with fasteners provided.
4. Caulk around base of threshold for moisture control.



THE PRODUCTS  
**YOU COUNT ON**  
THE PEOPLE  
**YOU TRUST**

[ngp.com](http://ngp.com)

FAX: (800) 255-7874  
QUOTES: [quotes@ngp.com](mailto:quotes@ngp.com)

**MEMPHIS**  
4985 East Raines Road  
Memphis, TN 38118

**CARSON CITY**  
3689 Arrowhead Drive  
Carson City, NV 89706