



# 602

## Nylon Brush Perimeter Seal

### PRODUCT CUT SHEET

PROJECT:
SUBMITTED BY:
DATE:
NOTES:

#### Material

Aluminum Alloy 6063, T5 Temper  
 Synthetic Polymer: Polyamide  
 Nylon Brush


- ▶ Excellent Abrasion Resistance, Flexibility and Memory
- ▶ Moisture-Resistant
- ▶ Retains Insecticides Well
- ▶ Temperature Range -70°F to 425°F
- ▶ BHMA Certified to ANSI/BHMA A156.22 Performance Tests For Heat, Cold, Air Infiltration and Smoke Infiltration in Most Common Profiles as Indicated by BHMA Certified Symbol
- ▶ REACH and RoHS Compliant
- ▶ Not Effective Against Water Penetration
- ▶ #6 X 3/4" Stainless Steel Sheet Metal Screws Furnished
- ▶ Screw Holes Slotted for Adjustment

#### Finishes

602A	Anodized Aluminum	Gray Brush
602A-BB	Anodized Aluminum	Black Brush
602DKB	Dark Bronze	Black Brush

#### Options

FATT - Fast Attach Tape



NGP-GKT-602-PCS-1123-A

#### NATIONAL GUARD PRODUCTS, INC.

##### MEMPHIS

4985 East Raines Road  
 Memphis, TN 38118

##### CARSON CITY

3689 Arrowhead Drive  
 Carson City, NV 89706

Fax: (800) 255-7874

Email: info@ngp.com

Quotes: quotes@ngp.com

Orders: orders@ngp.com

**ngp.com**  
 1-800-NGP-RUSH